

1700 – 2100 MHz Parabolic Grid

Features:

- Lightweight and durable construction.
- Feed input Type N as shown, for others see Note 2 below.
- Grid antenna designs offer lower wind-loading, typically reduced 40% or more from a comparable sized solid antenna without ice.
- Feed guy wires are included where necessary.
- Antenna features independent azimuth and elevation adjustment.
- Antenna Survival Ratings: 1 inch (25mm) of ice and 125 mph (201 kmh) wind.
- Antenna mounts to 4.5 in. OD (114 mm) (4 in. IPS) vertical pipe mast. Optional 2.38 in. - 4 in. OD (60 mm – 102 mm) mast-mount available for 4 ft (1.2 m) antenna.
- All mWAVE – Mark Grid Series antennas meet or exceed Standard ANSI/TIA-222.



1700 – 2100 MHz Parabolic Grid

Electrical Specifications

Frequency MHz	Model No.	Pol.	Size		Reg.	Gain, nominal dBi			HPBW Deg.	XPD dB	F/B dB	VSWR max	R.L. dB
			ft.	m		Low	Mid	High					
1700 – 2100	P-20A36GN-U	LP	3	0.9	-	21.6	22.6	23.5	10.7	35	26	1.5:1	14.0
1700 – 2100	P-20A48GN-U	LP	4	1.2	-	24.8	25.8	26.1	8.0	36	34	1.3:1	17.7 †
1700 – 2100	P-20A72GN-U	LP	6	1.8	B**	27.8	28.8	29.7	5.8	35	36	1.3:1	17.7 †
1700 – 2100	P-20A72GN-S	LP	6	1.8	B**	27.8	28.8	29.7	5.8	35	36	1.3:1	17.7 †
1700 – 2100	P-20A96GN-S	LP	8	2.4	A**	30.3	31.3	32.2	4.4	40	39	1.3:1	17.7 †
1700 – 2100	P-20A120GN-S	LP	10	3.0	A**	32.0	33.0	33.9	3.4	35	42	1.3:1	17.7 †
1700 – 2100	P-20A144GN-S	LP	12	3.7	A**	33.5	34.2	35.4	2.8	40	44	1.3:1	17.7 †
1700 – 2100	P-20A180GN-2	LP	15	4.6	A**	35.2	36.2	37.0	2.3	40	46	1.3:1	17.7 †

Notes:

- † Improved VSWR (R.L.) available.
- * Optional input connectors available.
 F = 7/8 EIA Flange Non-pressurized
 N = N-Female Connector Non-Pressurized
 E = 7/16 DIN Connector Non-Pressurized
 L = 7/8 EIA Flange Pressurized Low VSWR
 LN = N-Female Non-Pressurized Low VSWR
- ** U.S.F.C.C. Regulatory Standard Part 101.