

## 1990 - 2110 MHz Compak Grid

### Features:

- Lightweight and durable construction.
- Feed input Type N as shown, for others see Note 2 below.
- Grid antenna designs offer lower wind-loading, typically reduced 40% or more from a comparable sized solid antenna without ice.
- Feed guy wires are included where necessary.
- Antenna features independent azimuth and elevation adjustment.
- Antenna Survival Ratings: 1 inch (25mm) of ice and 125 mph (201 kmh) wind.
- Antenna mounts to 4.5 in. OD (114 mm) (4 in. IPS) vertical pipe mast. Optional 2.38 in. - 4 in. OD (60 mm – 102 mm) mast-mount available for 4 ft (1.2 m) antenna.
- All mWAVE – Mark Grid Series antennas meet or exceed Standard ANSI/TIA-222.



1990 - 2110 MHz Compak Grid

### Electrical Specifications

Frequency MHz	Model No.	Pol.	Size		Reg.	Gain, nominal dBi			HPBW Deg.	XPD dB	F/B dB	VSWR max	R.L. dB
			ft.	m		Low	Mid	High					
1990 - 2110	P-19A48KGN-U	LP	4	1.2	-	25.6	25.8	26.0	8.4	30	36	1.3:1	17.7 †
1990 - 2110	P-19A72KGN-U	LP	6	1.8	B**	29.2	29.3	29.5	5.6	30	38	1.2:1	20.8 †
1990 - 2110	P-19A96KGN-S	LP	8	2.4	A**	31.7	31.8	31.8	4.2	30	40	1.1:1	26.4 †

#### Notes:

- † Improved VSWR (R.L.) available.
- \* Optional input connectors available.  
 F = 7/8 EIA Flange Non-pressurized  
 N = N-Female Connector Non-Pressurized  
 E = 7/16 DIN Connector Non-Pressurized  
 L = 7/8 EIA Flange Pressurized Low VSWR  
 LN = N-Female Non-Pressurized Low VSWR
- \*\* U.S.F.C.C. Regulatory Standard Part 101.