

450 - 470 MHz Parabolic Grid

Features:

- Lightweight and durable construction.
- Feed input Type N as shown, for others see Note 2 below.
- Grid antenna designs offer lower wind-loading, typically reduced 40% or more from a comparable sized solid antenna without ice.
- Feed guy wires are included where necessary.
- Antenna features independent azimuth and elevation adjustment.
- Antenna Survival Ratings: 1 inch (25mm) of ice and 125 mph (201 kmh) wind.
- Antenna mounts to 4.5 in. OD (114 mm) (4 in. IPS) vertical pipe mast. Optional 2.38 in. - 4 in. OD (60 mm – 102 mm) mast-mount available for 4 ft (1.2 m) antenna.
- All mWAVE – Mark Grid Series antennas meet or exceed Standard ANSI/TIA-222.



450 - 470 MHz Parabolic Grid

Electrical Specifications

Frequency MHz	Model No.	Pol.	Size		Reg.	Gain, nominal dBi			HPBW Deg.	XPD dB	F/B dB	VSWR max	R.L. dB
			ft.	m		Low	Mid	High					
450 – 470	P-5A48GN-U	LP	4	1.2	n/a	12.9	13.1	13.3	34.0	13	16	1.5:1	14.0 †
450 – 470	P-5A72GN-U	LP	6	1.8	n/a	16.2	16.4	16.6	23.8	16	25	1.3:1	17.7 †
450 – 470	P-5A72GN-S	LP	6	1.8	n/a	16.2	16.4	16.6	23.8	16	25	1.3:1	17.7 †
450 – 470	P-5A96GN-S	LP	8	2.4	n/a	19.0	19.2	19.4	17.6	20	20	1.3:1	17.7 †
450 – 470	P-5A120GN-S	LP	10	3.0	n/a	21.3	21.7	21.7	14.0	22	22	1.3:1	17.7 †
450 – 470	P-5A144GN-S	LP	12	3.7	n/a	21.1	22.3	22.5	11.7	26	26	1.3:1	17.7 †
450 – 470	P-5A180GN-2	LP	15	4.6	n/a	23.9	24.1	24.3	10.3	28	28	1.3:1	17.7 †

Notes:

- † Improved VSWR (R.L.) available
- * Optional input connectors available.
 F = 7/8 EIA Flange Non-pressurized
 N = N-Female Connector Non-Pressurized
 E = 7/16 DIN Connector Non-Pressurized
 L = 7/8 EIA Flange Pressurized Low VSWR
 LN = N-Female Non-Pressurized Low VSWR