

## 875 - 960 MHz Parabolic Grid

### Features:

- Lightweight and durable construction.
- Feed input Type N as shown, for others see Note 2 below.
- Grid antenna designs offer lower wind-loading, typically reduced 40% or more from a comparable sized solid antenna without ice.
- Feed guy wires are included where necessary.
- Antenna features independent azimuth and elevation adjustment.
- Antenna Survival Ratings: 1 inch (25mm) of ice and 125 mph (201 kmh) wind.
- Antenna mounts to 4.5 in. OD (114 mm) (4 in. IPS) vertical pipe mast. Optional 2.38 in. - 4 in. OD (60 mm – 102 mm) mast-mount available for 4 ft (1.2 m) antenna.
- All mWAVE – Mark Grid Series antennas meet or exceed Standard ANSI/TIA-222.



875 - 960 MHz Parabolic Grid

### Electrical Specifications

Frequency MHz	Model No.	Pol.	Size		Reg.	Gain, nominal dBi			HPBW Deg.	XPD dB	F/B dB	VSWR max	R.L. dB
			ft.	m		Low	Mid	High					
875 – 960	P-8A48GN-U	LP	4	1.2	B**	18.9	19.3	19.7	17.7	22	23	1.5:1	14.0 †
875 – 960	P-8A72GN-U	LP	6	1.8	B**	21.6	22.0	22.4	12.3	19	22	1.3:1	17.7 †
875 – 960	P-8A72GN-S	LP	6	1.8	B**	21.6	22.0	22.4	12.3	19	22	1.3:1	17.7 †
875 – 960	P-8A96GN-S	LP	8	2.4	B**	24.2	24.5	25.0	9.5	19	24	1.3:1	17.7 †
875 – 960	P-8A120GN-S	LP	10	3.0	A**	26.6	27.0	27.4	6.4	20	27	1.3:1	17.7 †
875 – 960	P-8A144GN-S	LP	12	3.7	A**	26.9	27.3	27.7	6.4	26	26	1.3:1	17.7 †
875 – 960	P-8A180GN-2	LP	15	4.6	A**	28.4	28.8	29.2	4.9	30	30	1.3:1	17.7 †

### Notes:

- † Improved VSWR (R.L.) available.
- \* Optional input connectors available.  
 F = 7/8 EIA Flange Non-pressurized  
 N = N-Female Connector Non-Pressurized  
 E = 7/16 DIN Connector Non-Pressurized  
 L = 7/8 EIA Flange Pressurized Low VSWR  
 LN = N-Female Non-Pressurized Low VSWR
- \*\* U.S.F.C.C. Regulatory Standard Part 101.115.